

## **Upholstery Table Model KTK+ 4 with turnable table top:**



Upholstery working table KTK+ 4 with stainless steel turnable table top

Areas of application: → upholstery industrie for gluing, assembling packaging of upholsterd furniture and their components

and their component

Construction: 

The whole construction is made of a closed steel profiles ensuring proper durability and stiffness.

→ Steel powder coating adds an elegant look of the whole construction.
 → The whole mechanism, including pneumatics, protected by a steel folding

curtain 1.5 mm thick, which is powder coated too.

→ Pneumatic elements are hidden inside the table on a special slider that prevents contamination of the mechanism and pneumatic details while gluing furniture.

Table top: 
→ The work-top made of 18 mm thick coated board and covered with 2mm thick stainless steel remains clean a long time.

→ Steel tubes on the table top provide a minimal contact of furniture with the table surface

→ The table top is turnable in each table position

## **Technical Data:**

Base frame dimension:	700 mm x 700 mm
Turnable tabletop dimension:	1.200 mm x 750 mm
Maximum lifting height:	820 mm
Minimum lifting heigth:	450 mm
Maximum lifting capacity:	160 kg
Air pressure:	min. 6 bar – max. 8 bar
Power:	Pneumatic
Table weight:	ca. 150 kg

Subject to technical changes